

Rapid Freeze Device

series 20

TYPE CBU-30


Preserve fishes keeping their taste !

TYPE BFU-60

No missing freshness !

Movable & Rapid Freezing Container
up to ultra low temperature

-30°C



● **Low Cost**

More economical and efficient comparing with

● **Simple Operation**

One button switch operation

● **No limit for installation**

Operable wherever electric power supply is available

Generator can be provided, if

● **Leasing Available**

for required period of the use

-60°C

Seasonal Fishes

yellow tail
mackerel
hairtail
Spanish mackerel
barracuda
flatfish
sillaginoid
pacific saury
flounder
tuna
tilefish
bonita
salmon
sandfish
cuttle fish
oyster
snow crab
scallap



Advantage of introducing CBU30. BFU60

So far, most of fishes rapidly frozen at processing factory on shore have been processed only for canned, nobemaki, and fish feed for cultured fishes, due to too long time from unloading to freezing .

Then, this Movable & Rapidly Freezing Container "BFU-60" applicable up to ultra low temperature can shorten the time, thanks to its ability to freeze fishes moving the container near ships, and maintain similar grade of the freshness to the frozen fishes on ships.

Consequently, those frozen fishes can be also sold as the foodstuff for raw fishes (Sashimi).

It means that seasonal fishes, which could not have been tasted as raw fish (Sashimi) except real fresh one, can be served always to consumers on this frozen base.

In addition, this BFU-60 enable to supply seasonal fishes, unloaded anywhere in all seasons through a year, whenever and wherever, keeping those delicious taste.

◇Specification (CBU30)

Refrigeration Capacity CBU 30	ARI standard no.1110-69 Outside Temp. 38°C、Power Supply 60Hz		
	Return Air Temp.	Refrigeration Capacity	Electric Power
	-60°C	14.5KW	32KW
	-50°C	18.5KW	38KW
	-40°C	25KW	46KW
	-30°C	27KW	52KW
-20°C	28KW	53KW	

◇Specification(BFU60)

Refrigeration Capacity BFU 60	ARI standard no.1110-69 Outside Temp. 38°C、Power Supply 60Hz		
	Return Air Temp.	Refrigeration Capacity	Electric Power
	-60°C	22KW	75KW
	-50°C	38.5KW	80KW
	-40°C	50KW	85KW
	-30°C	60KW	90KW
-20°C	65KW	100KW	

Freezing Time, CBU30. BFU60

material		bare, openrack < 5 kg		ordinal carton,packaged by one plastic sheet < 5kg		doubled carton packaged by doubled plastic sheets < 5 kg	
	weight lkg	core temp	time	core temp	time	core temp	time
BFU-60D	18000	-25	24	-35	29	-38	32
	14000	-30	20	-38	24	-41	27
	10000	-35	16	-42	20	-44	22
	8000	-40	14	-46	17	-48	19
	4000	-50	10	-50	13	-50	15
CBU-30	weight kg	core temp	time	core temp	time	core temp	time
	9000	-25	24	-35	29	-37	32
	7000	-30	20	-38	24	-39	27
	5000	-35	16	-42	20	-43	22
	4000	-40	14	-46	17	-48	19
2000	-50	10	-50	13	-50	15	

Tokai Body
〒425-0067 43-1 Jicyouukesyo,Yaizu City Shizuoka Pref.,
Japan
TEL 81-54-623-1066
FAX 81-54-623-3454

Agency
MK ENGINEERING CO., LTD.
〒425-0041 1060 Ishizu, Yaizu City Shizuoka Pref., Japan
TEL 81-54-625-8360 FAX 81-54-625-8361
<http://www.mk-e.co.jp>